

SOILS

YANMAR

FUTURE IS NOW

SOLIS PUDDLING EXCELLENCE

4515 E

48HP cat.

Tractor Qualifiers Driving Savings

- Saving of nearly 1L/Hr in Rotavator
- Best speed for Rotavator application
- More depth and better pulverisation as compared to competition
- Highest Lift capacity in segment
- High power and better fuel efficiency at operating RPM
- Highest segment PTO HP



www.solis-yanmar.com
www.facebook.com/solistractorsindia
www.instagram.com/solistractorsindia

twitter.com/TractorsSolis
www.linkedin.com/company/solis-yanmar-tractors
https://www.youtube.com/channel/UCC_B_eQ50ni0dF9H8bG84tg



INTERNATIONAL TRACTORS LIMITED (Solis Tractors Division)

HEAD OFFICE: Plot No.10, Teri University, Vasant Kunj Institutional Area, Vasant Kunj, New Delhi-110070 | Tel: 91-11-66455200

MARKETING OFFICE: C-133A, Second Floor, Sector-2, Noida, U.P., India | Tel: 0120-4095860 | Email: support@solistractors.in

PLANT: International Tractors Limited, Village Chak Gujran, P.O. Piplanwala Jalandhar Road, Hoshiarpur, Punjab-146022

Tel: 91-1882-522220, 522221 | Fax: 91-1882-522222

JAPANESE TECHNOLOGY
Engine Expert

JAPANESE TECHNOLOGY
Transmission Expert

JAPANESE TECHNOLOGY
Hydraulics Expert

JAPANESE TECHNOLOGY
4WD Expert

Toll Free: 1800 1200 76547

www.solis-yanmar.com



JAPANESE TECHNOLOGY
Engine Expert **E3F**

Extra power and torque ensures operation with low ERPM drops. Hence, increasing productivity by 10-15%



SIX STAGE COOLING

Ensures continuous long hours working without load on engine, also without engine overheating

JAPANESE TECHNOLOGY
4WD
Expert

Turn plus & portable front axle ensures minimum turning radius and high ground clearance for rotavator puddling operation



INLINE MESH REVERSER

More PTO power in particular HP segment for more depth of cut with good pulverization



SPACIOUS PLATFORM

Flat platform with ergonomically designed levers and foot pedals. Extra cushioning seat with back rest ensuring long continuous hours with no fatigue.



DUAL CLUTCH

Dual clutch as standard fitment low effort of clutch operation. Also, it ensures that PTO does not stop even during change of gears or while turning at the end of pass.

SPECIFICATIONS - 4515E

	4WD	2WD	
Engine			
Engine HP	48		
No. of Cylinders	3		
Rated RPM	1900		
Max Torque (Nm)	205		
Air Cleaner	Dry		
Transmission			
Clutch Type	Dual / Single*		
Gear Box	10F+5R		
Max Rated Speed (kmph)	35.97		
Brake			
Brake Type	Multi Disc Outboard OIB		
Hydraulics			
Lift Capacity (kg)	2000 Cat		
3 Point Linkage	Cat 2 Implements		
Hydraulic Control	ADDC		
Steering			
Steering	Power Steering		
PTO			
PTO Standard RPM	540		
Tyre			
Tyre	Front	8*18 / 8.3*20*	6.5*16 / 6*16*
	Rear	13.6*28 / 14.9*28*	14.9*28 / 13.6*28*
Fuel Tank			
Capacity (L)	55		
Dimensions & Weight			
Total Weight (kg)	2310	2060	
Wheel Base (mm)	2110	2090	
Length (mm)	3630	3590	
Width (mm)	1860	1800 - 1830	